



Safety Data Sheet

Copyright, 2015, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	27-6198-9	Version number:	1.00
Revision date:	10/05/2015	Supersedes date:	Initial issue.
Transportation version number:	1.00 (11/05/2015)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

M2611, Hi-Tech Yellow Paste Wax (22-130B): M2611

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: Meguiars United Kingdom Limited, 3 Lamport Court, Heartlands, Daventry, Northants, NN11 8UF
Telephone: +44 (0)870 241 6696
E Mail: info@meguiars.co.uk
Website: www.meguiars.co.uk

1.4. Emergency telephone number

+44 (0)870 241 6696

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Flammable Solid, Category 1 - Flam. Sol. 1; H228
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

For full text of H phrases, see Section 16.

Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive

Indication of danger

Highly flammable; F; R11
Irritant; Xi; R38

R67

For full text of R phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols:

GHS02 (Flame) | GHS07 (Exclamation mark) |

Pictograms



Ingredient	CAS Nbr	% by Wt
Naphtha (petroleum), hydrotreated heavy	64742-48-9	30 - 60

HAZARD STATEMENTS:

H228	Flammable solid.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS

General:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

Prevention:

P210A	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260A	Do not breathe vapours.
P262	Do not get in eyes, on skin, or on clothing.
P271	Use only outdoors or in a well-ventilated area.

Response:

P332 + P313	If skin irritation occurs: Get medical advice/attention.
P331	Do NOT induce vomiting.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
P370 + P378G	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

10% of the mixture consists of components of unknown acute oral toxicity.

Contains 80% of components with unknown hazards to the aquatic environment.

Notes on labelling

M2611, Hi-Tech Yellow Paste Wax (22-130B): M2611

H304 is not required on the label due to the product's viscosity
Nota P applied to CAS 64742-48-9.

Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive**Symbol(s)**

Highly
Flammable



Irritant

Contains:

No ingredients are assigned to the label.

Risk phrases

R11 Highly flammable.
R38 Irritating to skin.
R67 Vapours may cause drowsiness and dizziness.

Safety phrases

S16 Keep away from sources of ignition - No Smoking.
S23A Do not breathe vapour.
S24 Avoid contact with skin.
S62 If swallowed, do not induce vomiting: Seek medical advice immediately and show this container or label.
S2 Keep out of the reach of children.

Notes on labelling

R65 is not required on the label due to the product's viscosity.

Nota P applied CASRN 64742-48-9.

R11 assigned based on test data indicating that this product is a flammable solid.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EU Inventory	% by Wt	Classification
Naphtha (petroleum), hydrotreated heavy	64742-48-9	EINECS 265-150-3	30 - 60	Xn:R65 - Nota 4,P (EU) Xi:R38; R67 (Self Classified) Asp. Tox. 1, H304 - Nota P (CLP) Skin Irrit. 2, H315; STOT SE 3, H336 (Self Classified)
Distillates (petroleum), hydrotreated light	64742-47-8	EINECS 265-149-8	< 20	Xn:R65 - Nota 4 (EU) R10; R66; R67 (Self Classified) Asp. Tox. 1, H304 (CLP) Flam. Liq. 3, H226; STOT SE 3, H336; EUH066 (Self Classified)

M2611, Hi-Tech Yellow Paste Wax (22-130B): M2611

Fatty acids, Montan-wax, Ethylene Esters	73138-45-1	EINECS 277-291-8	7 - 13	
Siloxanes and silicones, di-Me	63148-62-9		7 - 13	
ORGANIC SALT (NJTSR# 04499600-6842)	Trade Secret		5 - 10	
Carnauba Wax	8015-86-9	EINECS 232-399-4	3 - 7	
POLYMER WAX (NJTSR# 04499600-6843)	Trade Secret		0.5 - 1.5	
Paraffin Wax	8002-74-2	EINECS 232-315-6	0.5 - 1.5	

Please see section 16 for the full text of any R phrases and H statements referred to in this section

Please refer to section 15 for the any applicable Notas that have been applied to the above components

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide.

Carbon dioxide.

Condition

During combustion.

During combustion.

5.3. Advice for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Manufacturer determined	TWA:100 ppm	
Paraffin Wax	8002-74-2	UK HSC	TWA(as fume):2 mg/m ³ ;STEL(as fume):6 mg/m ³	
ORGANIC SALT (NJTSR# 04499600-6842)	Trade Secret	UK HSC	TWA:2 mg/m ³	

UK HSC : UK Health and Safety Commission

M2611, Hi-Tech Yellow Paste Wax (22-130B): M2611

TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety glasses with side shields.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Neoprene.	No data available	No data available

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Paste
Appearance/Odour	Light cream coloured paste with slight hydrocarbon odour
Odour threshold	<i>No data available.</i>
pH	<i>No data available.</i>
Boiling point/boiling range	198.9 °C
Melting point	<i>No data available.</i>
Flammability (solid, gas)	Flammable Solid: Category 1.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	65.6 °C

Autoignition temperature	No data available.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Vapour pressure	No data available.
Relative density	0.86 [Ref Std:WATER=1]
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Evaporation rate	No data available.
Vapour density	No data available.
Decomposition temperature	No data available.
Viscosity	> 0.1 Pa-s
Density	0.86 g/cm ³

9.2. Other information

Volatile organic compounds (VOC)	44.4 % weight
----------------------------------	---------------

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Strong oxidising agents.

Strong acids.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.	
-------------	--

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

M2611, Hi-Tech Yellow Paste Wax (22-130B): M2611

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

May be harmful in contact with skin.

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye contact

Vapours released during curing may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:**Single exposure may cause target organ effects:**

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE _{2,000 - 5,000} mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE _{20 - 50} mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Naphtha (petroleum), hydrotreated heavy	Inhalation-Vapor		LC ₅₀ estimated to be 20 - 50 mg/l
Naphtha (petroleum), hydrotreated heavy	Dermal	Rabbit	LD ₅₀ > 3,000 mg/kg
Naphtha (petroleum), hydrotreated heavy	Ingestion	Rat	LD ₅₀ > 5,000 mg/kg
Distillates (petroleum), hydrotreated light	Dermal	Rabbit	LD ₅₀ > 3,160 mg/kg
Distillates (petroleum), hydrotreated light	Inhalation-Dust/Mist (4 hours)	Rat	LC ₅₀ > 3.0 mg/l
Distillates (petroleum), hydrotreated light	Ingestion	Rat	LD ₅₀ > 5,000 mg/kg
Fatty acids, Montan-wax, Ethylene Esters	Ingestion	Rat	LD ₅₀ > 2,000 mg/kg
Siloxanes and silicones, di-Me	Dermal	Rabbit	LD ₅₀ > 19,400 mg/kg
Siloxanes and silicones, di-Me	Ingestion	Rat	LD ₅₀ > 17,000 mg/kg
Carnauba Wax	Dermal		LD ₅₀ estimated to be > 5,000 mg/kg
Carnauba Wax	Ingestion	Rat	LD ₅₀ > 8,800 mg/kg
Paraffin Wax	Dermal	Rabbit	LD ₅₀ > 5,000 mg/kg
Paraffin Wax	Ingestion	Rat	LD ₅₀ > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Naphtha (petroleum), hydrotreated heavy	Rabbit	Irritant
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
Carnauba Wax	Professio	No significant irritation

M2611, Hi-Tech Yellow Paste Wax (22-130B): M2611

	nal judgemen t	
--	----------------------	--

Serious Eye Damage/Irritation

Name	Species	Value
Naphtha (petroleum), hydrotreated heavy	Rabbit	No significant irritation
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
Carnauba Wax	Profession nal judgemen t	No significant irritation

Skin Sensitisation

Name	Species	Value
Naphtha (petroleum), hydrotreated heavy	Guinea pig	Not sensitising
Distillates (petroleum), hydrotreated light	Guinea pig	Not sensitising

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Naphtha (petroleum), hydrotreated heavy	In vivo	Not mutagenic
Naphtha (petroleum), hydrotreated heavy	In Vitro	Some positive data exist, but the data are not sufficient for classification
Distillates (petroleum), hydrotreated light	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Naphtha (petroleum), hydrotreated heavy	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Naphtha (petroleum), hydrotreated heavy	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Distillates (petroleum), hydrotreated light	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Naphtha (petroleum), hydrotreated heavy	Inhalation	Not toxic to development	Rat	NOAEL 2.4 mg/l	during organogenesis

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Naphtha (petroleum), hydrotreated heavy	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Naphtha (petroleum), hydrotreated heavy	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Naphtha (petroleum),	Inhalation	nervous system	Some positive data exist, but the	Dog	NOAEL 6.5	4 hours

M2611, Hi-Tech Yellow Paste Wax (22-130B): M2611

hydrotreated heavy			data are not sufficient for classification		mg/l	
Distillates (petroleum), hydrotreated light	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Distillates (petroleum), hydrotreated light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Naphtha (petroleum), hydrotreated heavy	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 4.6 mg/l	6 months
Naphtha (petroleum), hydrotreated heavy	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1.9 mg/l	13 weeks
Naphtha (petroleum), hydrotreated heavy	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.6 mg/l	90 days
Naphtha (petroleum), hydrotreated heavy	Inhalation	bone, teeth, nails, and/or hair blood liver muscles	All data are negative	Rat	NOAEL 5.6 mg/l	12 weeks
Naphtha (petroleum), hydrotreated heavy	Inhalation	heart	All data are negative	Multiple animal species	NOAEL 1.3 mg/l	90 days

Aspiration Hazard

Name	Value
Naphtha (petroleum), hydrotreated heavy	Aspiration hazard
Distillates (petroleum), hydrotreated light	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
ORGANIC SALT (NJTSR# 04499600-6842)	Trade Secret		Data not available or insufficient for classification			
Fatty acids, Montan-wax, Ethylene Esters	73138-45-1		Data not available or insufficient for classification			
POLYMER WAX (NJTSR#	Trade Secret		Data not available or insufficient for			

M2611, Hi-Tech Yellow Paste Wax (22-130B): M2611

04499600-6843)			classification			
Siloxanes and silicones, di-Me	63148-62-9		Data not available or insufficient for classification			
Naphtha (petroleum), hydrotreated heavy	64742-48-9		Data not available or insufficient for classification			
Distillates (petroleum), hydrotreated light	64742-47-8		Data not available or insufficient for classification			
Paraffin Wax	8002-74-2	Green algae	Experimental	96 hours	EC50	>1,000 mg/l
Paraffin Wax	8002-74-2	Water flea	Experimental	48 hours	EC50	>10,000 mg/l
Paraffin Wax	8002-74-2	Rainbow trout	Experimental	96 hours	LC50	>1,000 mg/l
Carnauba Wax	8015-86-9		Data not available or insufficient for classification			

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
ORGANIC SALT (NJTSR# 04499600-6842)	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Fatty acids, Montan-wax, Ethylene Esters	73138-45-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
POLYMER WAX (NJTSR# 04499600-6843)	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and silicones, di-Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Paraffin Wax	8002-74-2	Estimated Biodegradation	28 days	BOD	40 % weight	OECD 301F - Manometric respirometry
Carnauba Wax	8015-86-9	Modeled	28 days	BOD	82 % weight	OECD 301F -

M2611, Hi-Tech Yellow Paste Wax (22-130B): M2611

		Biodegradation				Manometric respirometry
--	--	----------------	--	--	--	-------------------------

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
ORGANIC SALT (NJTSR# 04499600-6842)	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Fatty acids, Montan-wax, Ethylene Esters	73138-45-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
POLYMER WAX (NJTSR# 04499600-6843)	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and silicones, di-Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

See Section 11.1 Information on toxicological effects

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the

M2611, Hi-Tech Yellow Paste Wax (22-130B): M2611

manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

EU waste code (product as sold)

20 01 13* Solvents

SECTION 14: Transportation information

ADR: UN1325; Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4.1; II; (E); F1.

IATA: UN1325; Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4.1; II.

IMDG: UN1325; Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4.1; II; EMS: F-A, S-G. (ENG)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact manufacturer for more information The components of this product are in compliance with the chemical notification requirements of TSCA.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

List of relevant R-phrases

R10	Flammable.
R11	Highly flammable.
R38	Irritating to skin.
R65	Harmful: May cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

Revision information:

No revision information is available.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

M2611, Hi-Tech Yellow Paste Wax (22-130B): M2611

Meguiar's, Inc. United Kingdom MSDSs are available at www.meguiars.co.uk